

BERGER Protecton

SIGMARK Sealant compd.

Scope

Hydrocarbon Resin based compound to be applied on concrete pavement to seal surface porosity and ensuring adhesion to the Thermoplastic Road Marking top coat.

Uses

A tie coat between concrete surface and Thermoplastic Road Marking compound.

Product Data

Consistency:	Smooth & uniform
Touch drying time	within 5 mins. Thermoplastic Road Marking compound to be applied when Coating is till tacky.
Application	by brush or spray.
Dry Film Thickness -	5-10 micron
Theoretical coverage	10 – 20 sq.mtrs.
Colour	clear.
Finish	smooth & Matt
Pack size	5ltrs

Recommended Thinner – Thinner 805

Storage Life: up to twelve months when stored in a cold dry place under the shed in sealed condition..

Surface to apply:

- Surface must be free from laitance & thoroughly dry and free from dust, rust, grease, oil, loose particles or earlier coating.
- Carry out all repair work like joints, sealing, filling of cracks, cavities and crevices with appropriate construction materials.

Application

Stir the container thoroughly & apply by brush or spray.

Paint System:

Concrete Road / Pavement: Sigmark Sealant – 1 coat at 5-10 mic
sigmark RM compound - 1 coat at 2.5 mm with
Drop on Glass Beads – Min. 250 to 350 gms / sq.m.

Precaution:

Avoid eye and skin contact. Safety goggles and protective gloves should be worn during handling. Not to apply paint on a wet surface. Sigmark RM should be applied when the sealant is still tacky.

Disclaimer

The information contained herein within this data sheet is based on information believed to be reliable at the time of its preparation. The Company will not be liable for loss or damage howsoever caused including liability for negligence, which may be suffered by the user of the data contained herein. It is the users' responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of results is implied since conditions of use are beyond our control.

Berger Paints India Ltd
BERGER HOUSE
129 Park Street
Calcutta-700 017
Tel: (033)22299724(5 lines)
222499754 (4 lines)
Fax: 99-33-222499729 / 9009

Data Sheet No: 149
Issue Date: April'04